

CL Vacuum Package

Exclusive coated lobes increase efficiency.

Commercial grade lobe style vacuum pump designed for the commercial dairy milking 12 - 18 hours a day. Popular sizes are available to fit most dairies - 7.5HP through to 30HP.

Key Features:

- Solid shaft and rotor assembly versus a two-piece, pinned design, stronger one-piece assembly out performs the competition.
- Exclusive internal coating, improves performance and reduces exhaust temperatures compared to uncoated pumps.
- Non-stick lobes release milk vapor build-up more readily.
- Helical timing gears versus straight spur gears, smoother operation with three gear touch points.
- Splash oil lubrication on both sides of the pump with no greasing required means longer time between compulsory maintenance.
- Viton lipseals - chemically resistant seals keep oil in and all other contaminants out.
- Powder coated paint process used on the steel frame to resist corrosion.



Commercial Grade Lobe style Vacuum Pump

CL PERFORMANCE SPECIFICATIONS

Description	RPM	L/Min@40KPA	L/Min@42.5KPA	L/Min@45KPA	L/Min@47.5KPA	L/Min@50KPA
5.5kW, 230V, 1ph or 3ph	1855	2500	2320	2160	1990	1840
7.5kW, 230V, 1ph or 3ph	2155	3120	2920	2730	2540	2360
11kW, 415V, 3ph	1842	5130	4830	4530	4240	3950
15kW, 415V, 3ph	2198	6480	6110	5770	5430	4980
18.5kW, 415V, 3ph	2500	7370	6950	6570	6180	5660

Air flow capacity measured at sea level at 68°F (20°C) ambient temperature